



## SOP range - Transformer starting

celduc relais has just launched a new range of peak switching SSR for transformers starting

Driving a saturable inductive load often generates high peaks of voltage which may damage semiconductors used in SSRs (which cause premature aging of relays) and breaking of protection devices.

A peak starting relay allows the starting current of the transformer to be reduced. So our new [SOP](#) range is designed for the start-up of transformer primary circuits and all saturated inductance coil loads preventing magnetising current peaks.

For the start-up of three-phase transformers, use our softstarters [SMCV/SMCW](#) or our three-phase proportional controllers [SVTA](#).

celduc products will be presented at the following exhibition :

### ELECTRONICS & APPLICATIONS

Utrecht - PAYS BAS  
Du 30 Mai au 1er Juin 2017  
Exposant : Elincom B.V.  
Hall 7 Booth 0033

Coming next month, our new range of three-phase SSR!



New

References available :

-[SOP65070](#) : 9A-AC56a

-[SOP69070](#) : 32A-AC56a

New buildings to challenge the future !



Building extension is nearing completion ...

## SOBR range - New two-phase Solid State Relays

Always ahead in solid-state control innovation, celduc® relais launch a new range of two phase Solid State Relays in okpac® housing with push-in spring power terminals.

References available :

-[SOBR965660](#) :  
2x24A - 24-600VAC - Ctrl 10-30VDC

-[SOBR965560](#) :  
2x24A - 24-600VAC - Ctrl 10-30VDC  
(version with one commun internal connection on input)



New



-Use the quick reference search "Find a product (name/ reference)" to download our data-sheets

-[CAD files 2D and 3D](#) are available in "Technical Library"

-Give us the information you want us to put in our « News » (exhibitions, special events, ...)

# SLA03220L - New Interface relay with very low leakage current



[SLA03220L](#) - 2A - 12-280VAC - Ctrl 18-32VDC  
- with very low leakage current.

Our SLIM range is 100% compatible with 5mm pitch electromechanical relays and is designed for most types of loads).

Tel. Sales department France:  
+33 (0) 4 77 53 90 20

Tel. Export Europe :  
+33 (0) 4 77 53 90 21

Tel. Export Asia :  
+ 33 (0) 4 77 53 90 19

Tel. Export America :  
+ 33 (0) 4 77 53 90 21

[celduc-relais@celduc.com](mailto:celduc-relais@celduc.com)

[www.celduc-relais.com](http://www.celduc-relais.com)

# MicroFusion range - up to 400A of reliable power control

MicroFusion, the latest generation of SCR power controllers up to 400Amps, concentrates all the know-how of Control Concept, Inc. and offers the greatest performances in the most compact design available on the market.

To download our catalogue [click here](#)



[Google+](#)



[Community](#)



You can delete your subscription at any time,  
(according to the article 34 of the french law concerning the computer science laws).

To unsubscribe to the mailing list - [Click here](#)